It's ultra portable, lightweight and easy-to-operate.
Introducing the world's most compact mobile printer, the
U2-mobile.

Ultra Lightweight
The world's lightest mobile printer, weighing only 1kg (2.21Lb)

Full-Color Large LCD Display
2.8" full-color LCD with LED back light

All IN ONE BOX
One tiny box with all the accessories you will ever need: U2 mobile, remote keypad, 2 high capactity rechargeable batteries, battery charger,SD card & SD card reader

SD Card Slot Design
Easy software upgrade and date backup

Ulta Portable
Capable of printing anywhere, at any angle, without ink leakage

Plug-n-Print
Ink cartridge design with no maintenance and downtime costs

Long Lasting Battery
7 hours of continuous printing with more than 200,000 characters

600 dpi(For U2 HD Only)
2X the resolution for printing crisp & precise HD barcodes. Now available on both U2 & U2-mobile

Remote Keypand
Pocket-size remote kaypad with user-friendly operation

More Ink Selections
Now you can print onto a variety of substrates using ANSER's new Inkfinity ink family

U2™ mobile

Print at anywhere at any angle !

- Ultra Portable
- Ultra Lightweight
- Long Lasting Battery

UNBEATABLE U2 HANDHELD

U2-Mobile Specifications

|	
Display	2.8" full-color LCD with LED backlight
LED Indicators	5 indicators: Alarm, Ink low, Print, Run, Remote on/off
Available Languages	English, French, German, Italian, Japanese, Korean, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese
Operation Menu	Digital Menu Selection (DMS) for easy operation
Input Device	Pocket-size IR remote keypad
Plug-n-Print Design	Hewlett-Packard TIJ 2.5 printing technology
Printable Images	Alphanumeric, logo, date/time, expiry date shift code, counter, lot-box code and barcode
Printable Lines & Heights	1, 2, 3, 4 lines. Total line height is limited to 12.7mm (0.5") Heights: 2.7mm, 3.6mm, 5.5mm, 8mm, 10mm, 12.7mm (0.11", 0.14", 0.22", 0.31", 0.39", 0.5")
Print Speed	57 meters (148 feet) / minute at 400 dpi horizontal resolution
Message Storage Capacity	Store up to 999 messages with SD card
Dimension (L/W/H)	212 x 135 x 120 (mm) / 8.3 x 5.3 x 4.7 (inch)
Weight	1Kg (2.20 lbs) – exclude cartridge and battery

Long Lasting Battery

Rated Capacity	2,200 mAh
Standard Voltage	11.1V
Input/Output Voltage	12.6V
Charging Voltage	12.6V
Charging Hours	2.5 hours
Charging Temperature Range	0°C – 45°C (32°F – 113°F)
Discharging Temperature Range	-10°C – 45°C (14°F – 113°F)
Dimension (L/W/H)	65 x 51 x 37 (mm) / 2.5 x 2 x 1.5 (inch)
Weight	165g (0.36Lb)
Cycle Life	More than 300 cycles
Continuous Printing Hours	7 hours
Stand-by Time	9 hours

Ink Solutions

A wide range of ink selections for printing on porous, semi-porous and non-porous substrates

Environment

Operating Temperature Range	5°C – 40°C (41°F – 104°F)

WWW.ANSER-U2.COM